

## MAYFIELD SIDs

## LONDON HEATHROW


## GENERAL INFORMATION

- 1 SIDs reflect Noise Preferential Routeings. See EGLL AD 2.21 for Noise Abatement Procedures.
- 2 Initial climb straight ahead to 580' QNH (500' QFE).
- 3 Cross Noise Monitoring Points not below 1080' QNH (1000' QFE) thereafter maintain minimum 4% climb gradient to 4000' (Note climb gradients greater than 4% may be required for ATC and airspace purposes) to comply with Noise Abatement requirements.
- 4 Callsign for RTF frequency used **when instructed** after take-off 'London Control'. Report callsign, SID designator, current altitude and cleared altitude on first contact with 'London Control'.
- 5 Maximum IAS 250KT en-route. MAY VOR at IAS 220KT or less.
- 6 Aircraft VOR or DME failure advise ATC and comply with ATC instructions.
- 7 MAY 2G first turn point: when I-LL DME is out of Service use LON 02.

NOT TO SCALE

TRANSITION ALT 6000'

**WARNING**  
Due to interaction with other routes do NOT climb above 5000ft until cleared by ATC.



AVERAGE  
TRACK MILEAGE  
TO MAY VOR

MAY 3F	40
MAY 2G	39
MAY 1H	36
MAY 2J	37
MAY 2K	38

SID	RWY	ROUTING (incl. Noise Preferential Routing)	ALTITUDES	AIRWAY ROUTE
MAY 3F 126-825	27R	Straight ahead to <b>LON 02</b> , then turn left onto QDM 140° to <b>EPM NDB</b> , then (but not before <b>LON 010</b> ) <b>MAY VOR</b> R317 to <b>MAY VOR</b> .	Cross <b>EPM NDB</b> at 5000' <b>MAY VOR</b> at 5000'.	For landing at LONDON GATWICK Airport only.
MAY 2G 126-825	27L	Straight ahead to <b>I-LL 01</b> , then turn left onto QDM 140° to <b>EPM NDB</b> , then (but not before <b>LON 010</b> ) <b>MAY VOR</b> R317 to <b>MAY VOR</b> .		
MAY 1H 126-825	23	Straight ahead to intercept QDM 153° to <b>EPM NDB</b> , then (but not before <b>LON 010</b> ) turn left onto <b>MAY VOR</b> R317 to <b>MAY VOR</b> .		
MAY 2J 126-825	09R	Straight ahead to <b>LON 02</b> , then turn right onto <b>LON VOR</b> R128 until <b>LON 03.5</b> , then turn right onto <b>MID VOR</b> R029 until <b>MID 020</b> , then turn left onto <b>MAY VOR</b> R317 to <b>MAY VOR</b> .	Cross <b>MID 020</b> at 5000' <b>MAY VOR</b> at 5000'.	
MAY 2K 126-825	09L	Straight ahead to <b>LON 01.5</b> , then turn right onto <b>LON VOR</b> R128 until <b>LON 03.5</b> then turn right onto <b>MID VOR</b> R029 until <b>MID 020</b> , then turn left onto <b>MAY VOR</b> R317 to <b>MAY VOR</b> .		

CHANGE RADIALS/TRACKS UPDATED.

AERO INFO DATE 5 MAR 02

**INTENTIONALLY    BLANK**